

Package: tidyfst (via r-universe)

September 16, 2024

Title Tidy Verbs for Fast Data Manipulation

Version 1.8.1

Depends R (>= 4.0.0)

Description A toolkit of tidy data manipulation verbs with 'data.table' as the backend. Combining the merits of syntax elegance from 'dplyr' and computing performance from 'data.table', 'tidyfst' intends to provide users with state-of-the-art data manipulation tools with least pain. This package is an extension of 'data.table'. While enjoying a tidy syntax, it also wraps combinations of efficient functions to facilitate frequently-used data operations.

URL <https://github.com/hope-data-science/tidyfst>,
<https://hope-data-science.github.io/tidyfst/>

BugReports <https://github.com/hope-data-science/tidyfst/issues>

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports data.table (>= 1.15.0), fst (>= 0.9.0), stringr (>= 1.5.0)

Suggests knitr, rmarkdown, nycflights13, pryr, tidyr, ggplot2, dplyr,
bench, testthat

VignetteBuilder knitr

Repository <https://hope-data-science.r-universe.dev>

RemoteUrl <https://github.com/hope-data-science/tidyfst>

RemoteRef HEAD

RemoteSha d70ead05dbf0163880fdb5dbb3dadf4267738427

Contents

<code>arrange_dt</code>	3
<code>as_fst</code>	4

bind_rows_dt	4
col_max	5
complete_dt	6
count_dt	7
cummean	8
distinct_dt	8
drop_na_dt	9
dummy_dt	11
export_fst	12
filter_dt	14
fst	15
group_by_dt	16
group_dt	17
import_fst_chunked	19
impute_dt	20
intersect_dt	21
in_dt	22
join	23
lead_dt	25
longer_dt	26
mat_df	27
mutate_dt	28
mutate_when	29
nest_dt	30
nth	32
object_size	33
pairwise_count_dt	34
percent	35
pkg_load	36
print_options	37
pull_dt	38
rec	39
relocate_dt	40
rename_dt	41
replace_dt	42
rn_col	43
round0	43
sample_dt	44
select_dt	45
separate_dt	47
slice_dt	48
sql_join	49
summarise_dt	50
sys_time_print	52
t_dt	53
uncount_dt	53
unite_dt	54
utf8_encoding	55

<code>arrange_dt</code>	3
<code>wider_dt</code>	55
<code>%notin%</code>	57
Index	58

<code>arrange_dt</code>	<i>Arrange entries in data.frame</i>
-------------------------	--------------------------------------

Description

Order the rows of a data frame rows by the values of selected columns.

Usage

```
arrange_dt(.data, ...)
```

Arguments

<code>.data</code>	<code>data.frame</code>
<code>...</code>	Arrange by what group? Minus symbol means arrange by descending order.

Value

`data.table`

See Also

[arrange](#)

Examples

```
iris %>% arrange_dt(Sepal.Length)

# minus for decreasing order
iris %>% arrange_dt(-Sepal.Length)

# arrange by multiple variables
iris %>% arrange_dt(Sepal.Length,Petal.Length)
```

as_fst	<i>Save a data.frame as a fst table</i>
--------	---

Description

This function first export the data.frame to a temporal file, and then parse it back as a fst table (class name is "fst_table").

Usage

```
as_fst(.data)
```

Arguments

.data A data.frame

Value

An object of class `fst_table`

Examples

```
## Not run:
iris %>%
  as_fst() -> iris_fst
iris_fst

## End(Not run)
```

bind_rows_dt	<i>Bind multiple data frames by row</i>
--------------	---

Description

Bind any number of data frames by row, making a longer result. Similar to `'dplyr::bind_rows'`, however, columns with same names but different data types would be coerced to a single proper data type.

Usage

```
bind_rows_dt(...)
```

Arguments

... Data frames to combine. Each argument can either be a data frame, a list that could be a data frame, or a list of data frames. Columns are matched by name, and any missing columns will be filled with `'NA'`.

Value

data.table

See Also

[bind_rows, rbindlist](#)

Examples

```
bind_rows_dt(iris[1:3,], iris[6:8,])

# data frames with same name but different type
# numeric data would be coerced to character data in this case
df1 <- data.frame(x = 1:2, y = letters[1:2])
df2 <- data.frame(x = 4:5, y = 1:2)
bind_rows_dt(df1, df2)
```

col_max

Get the column name of the max/min number each row

Description

For a data.frame with numeric values, add a new column specifying the column name of the first max/min value each row.

Usage

```
col_max(.data, ..., .name = "max_col")

col_min(.data, ..., .name = "min_col")
```

Arguments

.data	A data.frame with numeric column(s)
...	Variables for screening, could receive what 'select_dt' receives. When starts with '-' (minus symbol) or '!', return the negative columns.
.name	The column name of the new added column

Value

A data.table

References

<https://stackoverflow.com/questions/17735859/for-each-row-return-the-column-name-of-the-largest-value>

Examples

```

set.seed(199057)
DT <- data.table(matrix(sample(10, 100, TRUE), ncol=10))
DT
col_max(DT)
col_max(DT, V1:V3)
col_max(DT, .name = "max_col_name")
col_min(DT)
col_min(DT, 2:4)

col_max(iris)

```

complete_dt

*Complete a data frame with missing combinations of data***Description**

Turns implicit missing values into explicit missing values. All the combinations of column values (should be unique) will be constructed. Other columns will be filled with NAs or constant value.

Usage

```
complete_dt(.data, ..., fill = NA)
```

Arguments

.data	data.frame
...	Specification of columns to expand. The selection of columns is supported by the flexible select_dt . To find all unique combinations of provided columns, including those not found in the data, supply each variable as a separate argument. But the two modes (select the needed columns and fill outside values) could not be mixed, find more details in examples.
fill	Atomic value to fill into the missing cell, default uses NA.

Details

When the provided columns with addition data are of different length, all the unique combinations would be returned. This operation should be used only on unique entries, and it will always returned the unique entries.

If you supply fill parameter, these values will also replace existing explicit missing values in the data set.

Value

data.table

See Also[complete](#)**Examples**

```
df <- data.table(
  group = c(1:2, 1),
  item_id = c(1:2, 2),
  item_name = c("a", "b", "b"),
  value1 = 1:3,
  value2 = 4:6
)

df %>% complete_dt(item_id,item_name)
df %>% complete_dt(item_id,item_name,fill = 0)
df %>% complete_dt("item")
df %>% complete_dt(item_id=1:3)
df %>% complete_dt(item_id=1:3,group=1:2)
df %>% complete_dt(item_id=1:3,group=1:3,item_name=c("a","b","c"))
```

count_dt

*Count observations by group***Description**

Count the unique values of one or more variables.

Usage

```
count_dt(.data, ..., sort = TRUE, .name = "n")
```

```
add_count_dt(.data, ..., .name = "n")
```

Arguments

.data	data.table/data.frame data.frame will be automatically converted to data.table.
...	Variables to group by, could receive what 'select_dt' receives.
sort	logical. If TRUE result will be sorted in descending order by resulting variable.
.name	character. Name of resulting variable. Default uses "n".

Value

data.table

See Also[count](#)

Examples

```
iris %>% count_dt(Species)
iris %>% count_dt(Species, .name = "count")
iris %>% add_count_dt(Species)
iris %>% add_count_dt(Species, .name = "N")

mtcars %>% count_dt(cyl, vs)
mtcars %>% count_dt("cyl|vs")
mtcars %>% count_dt(cyl, vs, .name = "N", sort = FALSE)
mtcars %>% add_count_dt(cyl, vs)
mtcars %>% add_count_dt("cyl|vs")
```

cummean

Cumulative mean

Description

Returns a vector whose elements are the cumulative mean of the elements of the argument.

Usage

```
cummean(x)
```

Arguments

`x` a numeric or complex object, or an object that can be coerced to one of these.

Examples

```
cummean(1:10)
```

distinct_dt

Select distinct/unique rows in data.frame

Description

Select only unique/distinct rows from a data frame.

Usage

```
distinct_dt(.data, ..., .keep_all = FALSE, fromLast = FALSE)
```


Arguments

<code>.data</code>	<code>data.frame</code>
<code>...</code>	Optional variables to use when determining uniqueness. If there are multiple rows for a given combination of inputs, only the first row will be preserved. If omitted, will use all variables.
<code>.keep_all</code>	If TRUE, keep all variables in <code>data.frame</code> . If a combination of <code>...</code> is not distinct, this keeps the first row of values.
<code>fromLast</code>	Logical indicating if duplication should be considered from the reverse side. Defaults to FALSE.

Value

`data.table`

See Also

[distinct](#)

Examples

```
iris %>% distinct_dt()
iris %>% distinct_dt(Species)
iris %>% distinct_dt(Species, .keep_all = TRUE)
mtcars %>% distinct_dt(cyl, vs)
mtcars %>% distinct_dt(cyl, vs, .keep_all = TRUE)
mtcars %>% distinct_dt(cyl, vs, .keep_all = TRUE, fromLast = TRUE)
```

drop_na_dt

Dump, replace and fill missing values in data.frame

Description

A set of tools to deal with missing values in `data.frames`. It can dump, replace, fill (with next or previous observation) or delete entries according to their missing values.

Usage

```
drop_na_dt(.data, ...)

replace_na_dt(.data, ..., to)

delete_na_cols(.data, prop = NULL, n = NULL)

delete_na_rows(.data, prop = NULL, n = NULL)
```

```
fill_na_dt(.data, ..., direction = "down")
```

```
shift_fill(x, direction = "down")
```

Arguments

.data	data.frame
...	Columns to be replaced or filled. If not specified, use all columns.
to	What value should NA replace by?
prop	If proportion of NAs is larger than or equal to "prop", would be deleted.
n	If number of NAs is larger than or equal to "n", would be deleted.
direction	Direction in which to fill missing values. Currently either "down" (the default) or "up".
x	A vector with missing values to be filled.

Details

drop_na_dt drops the entries with NAs in specific columns. fill_na_dt fill NAs with observations ahead ("down") or below ("up"), which is also known as last observation carried forward (LOCF) and next observation carried backward(NOCB).

delete_na_cols could drop the columns with NA proportion larger than or equal to "prop" or NA number larger than or equal to "n", delete_na_rows works alike but deals with rows.

shift_fill could fill a vector with missing values.

Value

data.table

References

<https://stackoverflow.com/questions/23597140/how-to-find-the-percentage-of-nas-in-a-data-frame>

<https://stackoverflow.com/questions/2643939/remove-columns-from-dataframe-where-all-values-are-na>

<https://stackoverflow.com/questions/7235657/fastest-way-to-replace-nas-in-a-large-data-table>

See Also

[drop_na,replace_na, fill](#)

Examples

```
df <- data.table(x = c(1, 2, NA), y = c("a", NA, "b"))
df %>% drop_na_dt()
df %>% drop_na_dt(x)
df %>% drop_na_dt(y)
df %>% drop_na_dt(x,y)
```

```

df %>% replace_na_dt(to = 0)
df %>% replace_na_dt(x,to = 0)
df %>% replace_na_dt(y,to = 0)
df %>% replace_na_dt(x,y,to = 0)

df %>% fill_na_dt(x)
df %>% fill_na_dt() # not specified, fill all columns
df %>% fill_na_dt(y,direction = "up")

x = data.frame(x = c(1, 2, NA, 3), y = c(NA, NA, 4, 5),z = rep(NA,4))
x
x %>% delete_na_cols()
x %>% delete_na_cols(prop = 0.75)
x %>% delete_na_cols(prop = 0.5)
x %>% delete_na_cols(prop = 0.24)
x %>% delete_na_cols(n = 2)

x %>% delete_na_rows(prop = 0.6)
x %>% delete_na_rows(n = 2)

# shift_fill
y = c("a",NA,"b",NA,"c")

shift_fill(y) # equals to
shift_fill(y,"down")

shift_fill(y,"up")

```

dummy_dt

Fast creation of dummy variables

Description

Quickly create dummy (binary) columns from character and factor type columns in the inputted data (and numeric columns if specified.) This function is useful for statistical analysis when you want binary columns rather than character columns.

Usage

```
dummy_dt(.data, ..., longname = TRUE)
```

Arguments

.data	data.frame
...	Columns you want to create dummy variables from. Very flexible, find in the examples.
longname	logical. Should the output column be labeled with the original column name? Default uses TRUE.

Details

If no columns provided, will return the original data frame. When NA exist in the input column, they would also be considered. If the input character column contains both NA and string "NA", they would be merged.

This function is inspired by **fastDummies** package, but provides simple and precise usage, whereas `fastDummies::dummy_cols` provides more features for statistical usage.

Value

data.table

References

<https://stackoverflow.com/questions/18881073/creating-dummy-variables-in-r-data-table>

See Also

[dummy_cols](#)

Examples

```
iris %>% dummy_dt(Species)
iris %>% dummy_dt(Species,longname = FALSE)

mtcars %>% head() %>% dummy_dt(vs,am)
mtcars %>% head() %>% dummy_dt("cyl|gear")

# when there are NAs in the column
df <- data.table(x = c("a", "b", NA, NA),y = 1:4)
df %>%
  dummy_dt(x)

# when NA and "NA" both exist, they would be merged
df <- data.table(x = c("a", "b", NA, "NA"),y = 1:4)
df %>%
  dummy_dt(x)
```

export_fst

Read and write fst files

Description

Wrapper for [read_fst](#) and [write_fst](#) from **fst**, but use a different default. For data import, always return a data.table. For data export, always compress the data to the smallest size.

Usage

```
export_fst(x, path, compress = 100, uniform_encoding = TRUE)
```

```
import_fst(
  path,
  columns = NULL,
  from = 1,
  to = NULL,
  as.data.table = TRUE,
  old_format = FALSE
)
```

Arguments

<code>x</code>	a data frame to write to disk
<code>path</code>	path to fst file
<code>compress</code>	value in the range 0 to 100, indicating the amount of compression to use. Lower values mean larger file sizes. The default compression is set to 50.
<code>uniform_encoding</code>	If 'TRUE', all character vectors will be assumed to have elements with equal encoding. The encoding (latin1, UTF8 or native) of the first non-NA element will be used as encoding for the whole column. This will be a correct assumption for most use cases. If 'uniform.encoding' is set to 'FALSE', no such assumption will be made and all elements will be converted to the same encoding. The latter is a relatively expensive operation and will reduce write performance for character columns.
<code>columns</code>	Column names to read. The default is to read all columns.
<code>from</code>	Read data starting from this row number.
<code>to</code>	Read data up until this row number. The default is to read to the last row of the stored dataset.
<code>as.data.table</code>	If TRUE, the result will be returned as a <code>data.table</code> object. Any keys set on dataset <code>x</code> before writing will be retained. This allows for storage of sorted datasets. This option requires <code>data.table</code> package to be installed.
<code>old_format</code>	must be FALSE, the old fst file format is deprecated and can only be read and converted with fst package versions 0.8.0 to 0.8.10.

Value

'import_fst' returns a `data.table` with the selected columns and rows. 'export_fst' writes 'x' to a 'fst' file and invisibly returns 'x' (so you can use this function in a pipeline).

See Also

[read_fst](#)

Examples

```
## Not run:
export_fst(iris,"iris_fst_test.fst")
iris_dt = import_fst("iris_fst_test.fst")
iris_dt
unlink("iris_fst_test.fst")

## End(Not run)
```

filter_dt

Filter entries in data.frame

Description

Choose rows where conditions are true.

Usage

```
filter_dt(.data, ...)
```

Arguments

<code>.data</code>	data.frame
<code>...</code>	List of variables or name-value pairs of summary/modifications functions.

Value

data.table

See Also

[filter](#)

Examples

```
iris %>% filter_dt(Sepal.Length > 7)
iris %>% filter_dt(Sepal.Length == max(Sepal.Length))

# comma is not supported in tidyfst after v0.9.8
# which means you can't use:
## Not run:
iris %>% filter_dt(Sepal.Length > 7, Sepal.Width > 3)

## End(Not run)
# use following code instead
iris %>% filter_dt(Sepal.Length > 7 & Sepal.Width > 3)
```

fst	<i>Parse, inspect and extract data.table from fst file</i>
-----	--

Description

A toolkit of APIs for reading fst file as `data.table`, could select by column, row and conditional filtering.

Usage

```
parse_fst(path)

slice_fst(ft, row_no)

select_fst(ft, ...)

filter_fst(ft, ...)

summary_fst(ft)
```

Arguments

path	path to fst file
ft	An object of class <code>fst_table</code> , returned by <code>parse_fst</code>
row_no	An integer vector (Positive)
...	The filter conditions

Details

`summary_fst` could provide some basic information about the fst table.

Value

`parse_fst` returns a `fst_table` class.
`select_fst` and `filter_fst` returns a `data.table`.

See Also

[fst](#), [metadata_fst](#)

Examples

```
## Not run:
fst::write_fst(iris, "iris_test.fst")
# parse the file but not reading it
parse_fst("iris_test.fst") -> ft
ft
```

```

class(ft)
lapply(ft,class)
names(ft)
dim(ft)
summary_fst(ft)

# get the data by query
ft %>% slice_fst(1:3)
ft %>% slice_fst(c(1,3))

ft %>% select_fst(Sepal.Length)
ft %>% select_fst(Sepal.Length,Sepal.Width)
ft %>% select_fst("Sepal.Length")
ft %>% select_fst(1:3)
ft %>% select_fst(1,3)
ft %>% select_fst("Se")
ft %>% select_fst("nothing")
ft %>% select_fst("Se|Sp")
ft %>% select_fst(cols = names(iris)[2:3])

ft %>% filter_fst(Sepal.Width > 3)
ft %>% filter_fst(Sepal.Length > 6 , Species == "virginica")
ft %>% filter_fst(Sepal.Length > 6 & Species == "virginica" & Sepal.Width < 3)

unlink("iris_test.fst")

## End(Not run)

```

group_by_dt

Group by variable(s) and implement operations

Description

Carry out data manipulation within specified groups. Different from `group_dt`, the implementation is split into two operations, namely grouping and implementation.

Using `setkey` and `setkeyv` in **data.table** to carry out `group_by`-like functionalities in **dplyr**. This is not only convenient but also efficient in computation.

Usage

```
group_by_dt(.data, ..., cols = NULL)
```

```
group_exe_dt(.data, ...)
```

Arguments

`.data` A data frame

... Variables to group by for group_by_dt, namely the columns to sort by. Do not quote the column names. Any data manipulation arguments that could be implemented on a data.frame for group_exe_dt. It can receive what select_dt receives.

cols A character vector of column names to group by.

Details

group_by_dt and group_exe_dt are a pair of functions to be used in combination. It utilizes the feature of key setting in data.table, which provides high performance for group operations, especially when you have to operate by specific groups frequently.

Value

A data.table with keys

Examples

```
# aggregation after grouping using group_exe_dt
as.data.table(iris) -> a
a %>%
  group_by_dt(Species) %>%
  group_exe_dt(head(1))

a %>%
  group_by_dt(Species) %>%
  group_exe_dt(
    head(3) %>%
    summarise_dt(sum = sum(Sepal.Length))
  )

mtcars %>%
  group_by_dt("cyl|am") %>%
  group_exe_dt(
    summarise_dt(mpg_sum = sum(mpg))
  )
# equals to
mtcars %>%
  group_by_dt(cols = c("cyl", "am")) %>%
  group_exe_dt(
    summarise_dt(mpg_sum = sum(mpg))
  )
```

group_dt

Data manipulation within groups

Description

Carry out data manipulation within specified groups.

Usage

```
group_dt(.data, by = NULL, ...)

rowwise_dt(.data, ...)
```

Arguments

.data	A data.frame
by	Variables to group by, unquoted name of grouping variable or list of unquoted names of grouping variables.
...	Any data manipulation arguments that could be implemented on a data.frame.

Details

If you want to use `summarise_dt` and `mutate_dt` in `group_dt`, it is better to use the "by" parameter in those functions, that would be much faster because you don't have to use `.SD` (which takes extra time to copy).

Value

data.table

References

<https://stackoverflow.com/questions/36802385/use-by-each-row-for-data-table>

Examples

```
iris %>% group_dt(by = Species, slice_dt(1:2))
iris %>% group_dt(Species, filter_dt(Sepal.Length == max(Sepal.Length)))
iris %>% group_dt(Species, summarise_dt(new = max(Sepal.Length)))

# you can pipe in the `group_dt`
iris %>% group_dt(Species,
                 mutate_dt(max = max(Sepal.Length)) %>%
                 summarise_dt(sum = sum(Sepal.Length)))

# for users familiar with data.table, you can work on .SD directly
# following codes get the first and last row from each group
iris %>%
  group_dt(
    by = Species,
    rbind(.SD[1], .SD[.N])
  )

#' # for summarise_dt, you can use "by" to calculate within the group
mtcars %>%
  summarise_dt(
    disp = mean(disp),
    hp = mean(hp),
```

```

    by = cyl
  )

  # but you could also, of course, use group_dt
  mtcars %>%
    group_dt(by =.(vs,am),
             summarise_dt(avg = mean(mpg)))

  # and list of variables could also be used
  mtcars %>%
    group_dt(by =list(vs,am),
             summarise_dt(avg = mean(mpg)))

# examples for `rowwise_dt`
df <- data.table(x = 1:2, y = 3:4, z = 4:5)

df %>% mutate_dt(m = mean(c(x, y, z)))

df %>% rowwise_dt(
  mutate_dt(m = mean(c(x, y, z)))
)

```

import_fst_chunked *Read a fst file by chunks*

Description

For ‘import_fst_chunked’, if a large fst file which could not be imported into the memory all at once, this function could read the fst file by chunks and preprocessed the chunk to ensure the results yielded by the chunks are small enough to be summarised in the end. For ‘get_fst_chunk_size’, this function can measure the memory used by a specified row number.

Usage

```

import_fst_chunked(
  path,
  chunk_size = 10000L,
  chunk_f = identity,
  combine_f = rbindlist
)

get_fst_chunk_size(path, nrows)

```

Arguments

path	Path to fst file
chunk_size	Integer. The number of rows to include in each chunk
chunk_f	A function implemented on every chunk.

combine_f A function to aggregate all the elements from the list of results from chunks.
 nrows Number of rows to test.

Value

For 'import_fst_chunked', default to the whole data.frame in data.table. Could be adjusted to any type. For 'get_fst_chunk_size', return the file size.

See Also

[read_csv_chunked](#)

Examples

```
## Not run:
# Generate some random data frame with 10 million rows and various column types
nr_of_rows <- 1e7
df <- data.frame(
  Logical = sample(c(TRUE, FALSE, NA), prob = c(0.85, 0.1, 0.05), nr_of_rows, replace = TRUE),
  Integer = sample(1L:100L, nr_of_rows, replace = TRUE),
  Real = sample(sample(1:10000, 20) / 100, nr_of_rows, replace = TRUE),
  Factor = as.factor(sample(labels(UScitiesD), nr_of_rows, replace = TRUE))
)

# Write the file to disk
fst_file <- tempfile(fileext = ".fst")
write_fst(df, fst_file)

# Get the size of 10000 rows
get_fst_chunk_size(fst_file, 1e4)

# File all rows that Integer == 7 by chunks
import_fst_chunked(fst_file, chunk_f = \"(x) x[Integer==7]

## End(Not run)
```

impute_dt

Impute missing values with mean, median or mode

Description

Impute the columns of data.frame with its mean, median or mode.

Usage

```
impute_dt(.data, ..., .func = "mode")
```

Arguments

<code>.data</code>	A data.frame
<code>...</code>	Columns to select
<code>.func</code>	Character, "mode" (default), "mean" or "median". Could also define it by one-self.

Value

A data.table

Examples

```
Pclass <- c(3, 1, 3, 1, 3, 2, 2, 3, NA, NA)
Sex <- c('male', 'male', 'female', 'female', 'female',
        'female', NA, 'male', 'female', NA)
Age <- c(22, 38, 26, 35, NA,
        45, 25, 39, 28, 40)
SibSp <- c(0, 1, 3, 1, 2, 3, 2, 2, NA, 0)
Fare <- c(7.25, 71.3, 7.92, NA, 8.05, 8.46, 51.9, 60, 32, 15)
Embarked <- c('S', NA, 'S', 'Q', 'Q', 'S', 'C', 'S', 'C', 'S')
data <- data.frame('Pclass' = Pclass,
                  'Sex' = Sex, 'Age' = Age, 'SibSp' = SibSp,
                  'Fare' = Fare, 'Embarked' = Embarked)

data
data %>% impute_dt() # default uses "mode" as `.func`
data %>% impute_dt(is.numeric, .func = "mean")
data %>% impute_dt(is.numeric, .func = "median")

my_fun = function(x){
  x[is.na(x)] = (max(x, na.rm = TRUE) - min(x, na.rm = TRUE))/2
  x
}
data %>% impute_dt(is.numeric, .func = my_fun)
```

 intersect_dt

Set operations for data frames

Description

Wrappers of set operations in **data.table**. Only difference is it could be applied to non-data.table data frames by recognizing and coercing them to data.table automatically.

Usage

```
intersect_dt(x, y, all = FALSE)
```

```
union_dt(x, y, all = FALSE)
```

```
setdiff_dt(x, y, all = FALSE)
```

```
setequal_dt(x, y, all = TRUE)
```

Arguments

x	A data.frame
y	A data.frame
all	Logical. When FALSE (default), removes duplicate rows on the result.

Value

A data.table

See Also

[setops](#)

Examples

```
x = iris[c(2,3,3,4),]
x2 = iris[2:4,]
y = iris[c(3:5),]

intersect_dt(x, y)           # intersect
intersect_dt(x, y, all=TRUE) # intersect all
setdiff_dt(x, y)           # except
setdiff_dt(x, y, all=TRUE) # except all
union_dt(x, y)             # union
union_dt(x, y, all=TRUE)  # union all
setequal_dt(x, x2, all=FALSE) # setequal
setequal_dt(x, x2)        # setequal all
```

in_dt

Short cut to data.table

Description

To use facilities provided by **data.table**, but do not have to load **data.table** package.

Usage

```
in_dt(.data, ...)
```

```
as_dt(.data)
```

Arguments

.data	A data.frame
...	Recieve B in data.table's A[B] syntax.

Details

The `as_dt` could turn any data frame to `data.table` class. If the data is not a data frame, return error.

The `in_dt` function creates a virtual environment in `data.table`, it could be piped well because it still follows the principals of **tidyfst**, which are: (1) Never use in place replacement and (2) Always recieves a data frame (`data.frame/tibble/data.table`) and returns a `data.table`. Therefore, the in place functions like `:=` will still return the results.

See Also

[data.table](#)

Examples

```
iris %>% as_dt()
iris %>% in_dt(order(-Sepal.Length), .SD[.N], by=Species)
```

join

Join tables

Description

The mutating joins add columns from 'y' to 'x', matching rows based on the keys:

* `'inner_join_dt()'`: includes all rows in 'x' and 'y'. * `'left_join_dt()'`: includes all rows in 'x'. * `'right_join_dt()'`: includes all rows in 'y'. * `'full_join_dt()'`: includes all rows in 'x' or 'y'.

Filtering joins filter rows from 'x' based on the presence or absence of matches in 'y':

* `'semi_join_dt()'` return all rows from 'x' with a match in 'y'. * `'anti_join_dt()'` return all rows from 'x' without a match in 'y'.

Usage

```

inner_join_dt(x, y, by = NULL, on = NULL, suffix = c(".x", ".y"))

left_join_dt(x, y, by = NULL, on = NULL, suffix = c(".x", ".y"))

right_join_dt(x, y, by = NULL, on = NULL, suffix = c(".x", ".y"))

full_join_dt(x, y, by = NULL, on = NULL, suffix = c(".x", ".y"))

anti_join_dt(x, y, by = NULL, on = NULL)

semi_join_dt(x, y, by = NULL, on = NULL)

```

Arguments

<code>x</code>	A <code>data.table</code>
<code>y</code>	A <code>data.table</code>
<code>by</code>	(Optional) A character vector of variables to join by. If 'NULL', the default, <code>*_join_dt()</code> will perform a natural join, using all variables in common across 'x' and 'y'. A message lists the variables so that you can check they're correct; suppress the message by supplying 'by' explicitly. To join by different variables on 'x' and 'y', use a named vector. For example, <code>by = c("a" = "b")</code> will match 'x\$a' to 'y\$b'. To join by multiple variables, use a vector with length > 1. For example, <code>by = c("a", "b")</code> will match 'x\$a' to 'y\$a' and 'x\$b' to 'y\$b'. Use a named vector to match different variables in 'x' and 'y'. For example, <code>by = c("a" = "b", "c" = "d")</code> will match 'x\$a' to 'y\$b' and 'x\$c' to 'y\$d'.
<code>on</code>	(Optional) Indicate which columns in x should be joined with which columns in y. Examples included: 1.. <code>by = c("a", "b")</code> (this is a must for <code>set_full_join_dt</code>); 2.. <code>by = c(x1="y1", x2="y2")</code> ; 3.. <code>by = c("x1==y1", "x2==y2")</code> ; 4.. <code>by = c("a", V2="b")</code> ; 5.. <code>by = .(a, b)</code> ; 6.. <code>by = c("x>=a", "y<=b")</code> or <code>by = .(x>=a, y<=b)</code> .
<code>suffix</code>	If there are non-joined duplicate variables in x and y, these suffixes will be added to the output to disambiguate them. Should be a character vector of length 2.

Value

A `data.table`

Examples

```

workers = fread("
  name company
  Nick Acme
  John Ajax
  Daniela Ajax
")

positions = fread("

```



```

      name position
      John designer
      Daniela engineer
      Cathie manager
    ")

workers %>% inner_join_dt(positions)
workers %>% left_join_dt(positions)
workers %>% right_join_dt(positions)
workers %>% full_join_dt(positions)

# filtering joins
workers %>% anti_join_dt(positions)
workers %>% semi_join_dt(positions)

# To suppress the message, supply 'by' argument
workers %>% left_join_dt(positions, by = "name")

# Use a named 'by' if the join variables have different names
positions2 = setNames(positions, c("worker", "position")) # rename first column in 'positions'
workers %>% inner_join_dt(positions2, by = c("name" = "worker"))

# the syntax of 'on' could be a bit different
workers %>% inner_join_dt(positions2, on = "name==worker")

```

lead_dt

Fast lead/lag for vectors

Description

Find the "next" or "previous" values in a vector. It has wrapped **data.table**'s shift function.

Usage

```
lead_dt(x, n = 1L, fill = NA)
```

```
lag_dt(x, n = 1L, fill = NA)
```

Arguments

x	A vector
n	a positive integer of length 1, giving the number of positions to lead or lag by. Default uses 1
fill	Value to use for padding when the window goes beyond the input length. Default uses NA

Value

A vector

See Also

[lead,shift](#)

Examples

```
lead_dt(1:5)
lag_dt(1:5)
lead_dt(1:5,2)
lead_dt(1:5,n = 2,fill = 0)
```

<code>longer_dt</code>	<i>Pivot data from wide to long</i>
------------------------	-------------------------------------

Description

Turning a wide table to its longer form. It takes multiple columns and collapses into key-value pairs.

Usage

```
longer_dt(.data, ..., name = "name", value = "value", na.rm = FALSE)
```

Arguments

<code>.data</code>	A data.frame
<code>...</code>	Pattern for unchanged group or unquoted names. Pattern can accept regular expression to match column names. It can receive what <code>select_dt</code> receives.
<code>name</code>	Name for the measured variable names column. The default name is 'name'.
<code>value</code>	Name for the molten data values column(s). The default name is 'value'.
<code>na.rm</code>	If TRUE, NA values will be removed from the molten data.

Value

A data.table

See Also

[wider_dt](#), [melt](#), [pivot_longer](#)

Examples

```
## Example 1:
stocks = data.frame(
  time = as.Date('2009-01-01') + 0:9,
  X = rnorm(10, 0, 1),
  Y = rnorm(10, 0, 2),
  Z = rnorm(10, 0, 4)
)
```

```
stocks
```

```
stocks %>%
  longer_dt(time)
```

```
stocks %>%
  longer_dt("ti")
```

```
# Example 2:
```

```
library(tidyr)
```

```
billboard %>%
  longer_dt(
    -"wk",
    name = "week",
    value = "rank",
    na.rm = TRUE
  )
```

```
# or use:
billboard %>%
  longer_dt(
    artist, track, date.entered,
    name = "week",
    value = "rank",
    na.rm = TRUE
  )
```

```
# or use:
billboard %>%
  longer_dt(
    1:3,
    name = "week",
    value = "rank",
    na.rm = TRUE
  )
```

Description

Convenient functions to implement conversion between tidy table and named matrix.

Usage

```
mat_df(m)
```

```
df_mat(df, row, col, value)
```

Arguments

m	A matrix
df	A data.frame with at least 3 columns, one for row name, one for column name, and one for values. The names for column and row should be unique.
row	Unquoted expression of column name for row
col	Unquoted expression of column name for column
value	Unquoted expression of column name for values

Value

For `mat_df`, a data.frame. For `df_mat`, a named matrix.

Examples

```
mm = matrix(c(1:8,NA),ncol = 3,dimnames = list(letters[1:3],LETTERS[1:3]))
mm
tdf = mat_df(mm)
tdf
mat = df_mat(tdf,row,col,value)
setequal(mm,mat)

tdf %>%
  setNames(c("A","B","C")) %>%
  df_mat(A,B,C)
```

mutate_dt

Mutate columns in data.frame

Description

Adds or updates columns in data.frame.

Usage

```
mutate_dt(.data, ..., by)
```

```
transmute_dt(.data, ..., by)
```

Arguments

`.data` data.frame
`...` List of variables or name-value pairs of summary/modifications functions.
`by` (Optional) Mutate by what group?

Value

data.table

See Also

[mutate](#)

Examples

```
iris %>% mutate_dt(one = 1, Sepal.Length = Sepal.Length + 1)
iris %>% transmute_dt(one = 1, Sepal.Length = Sepal.Length + 1)
# add group number with symbol `GRP`
iris %>% mutate_dt(id = 1:.N, grp = .GRP, by = Species)
```

mutate_when

Conditional update of columns in data.table

Description

Update or add columns when the given condition is met.

`mutate_when` integrates `mutate` and `case_when` in **dplyr** and make a new tidy verb for `data.table`.
`mutate_vars` is a super function to do updates in specific columns according to conditions.

Usage

```
mutate_when(.data, when, ..., by)
```

```
mutate_vars(.data, .cols = NULL, .func, ..., by)
```

Arguments

`.data` data.frame
`when` An object which can be coerced to logical mode
`...` Name-value pairs of expressions for `mutate_when`. Additional parameters to be passed to parameter `'func'` in `mutate_vars`.
`by` (Optional) Mutate by what group?
`.cols` Any types that can be accepted by `select_dt`.
`.func` Function to be run within each column, should return a value or vectors with same length.

Value

data.table

See Also

[select_dt](#), [case_when](#)

Examples

```
iris[3:8,]
iris[3:8,] %>%
  mutate_when(Petal.Width == .2,
              one = 1, Sepal.Length=2)

iris %>% mutate_vars("Petal", scale)
iris %>% mutate_vars(is.numeric, scale)
iris %>% mutate_vars(!is.factor, scale)
iris %>% mutate_vars(1:2, scale)
iris %>% mutate_vars(.func = as.character)
```

nest_dt

Nest and unnest

Description

Create or melt list columns in data.frame.

Analogous function for nest and unnest in **tidyr**. `unnest_dt` will automatically remove other list-columns except for the target list-columns (which would be unnested later). Also, `squeeze_dt` is designed to merge multiple columns into list column.

Usage

```
nest_dt(.data, ..., mcols = NULL, .name = "ndt")
```

```
unnest_dt(.data, ...)
```

```
squeeze_dt(.data, ..., .name = "ndt")
```

```
chop_dt(.data, ...)
```

```
unchop_dt(.data, ...)
```

Arguments

`.data` data.table, nested or unnested

`...` The variables for nest group(for `nest_dt`), columns to be nested(for `squeeze_dt` and `chop_dt`), or column(s) to be unnested(for `unnest_dt`). Could receive anything that [select_dt](#) could receive.

mcols	Name-variable pairs in the list, form like
.name	Character. The nested column name. Defaults to "ndt". <code>list(petal="^Pe", sepal="^Se")</code> , see example.

Details

In the `nest_dt`, the data would be nested to a column named 'ndt', which is short for nested data.table.

The `squeeze_dt` would not remove the original columns.

The `unchop_dt` is the reverse operation of `chop_dt`.

These functions are experiencing the experimental stage, especially the `unnest_dt`. If they don't work on some circumstances, try **tidyr** package.

Value

data.table, nested or unnested

References

<https://www.r-bloggers.com/much-faster-unnesting-with-data-table/>

<https://stackoverflow.com/questions/25430986/create-nested-data-tables-by-collapsing-rows-into-new-data-tables>

See Also

[nest](#), [chop](#)

Examples

```
# examples for nest_dt
# nest by which columns?
mtcars %>% nest_dt(cyl)
mtcars %>% nest_dt("cyl")
mtcars %>% nest_dt(cyl,vs)
mtcars %>% nest_dt(vs:am)
mtcars %>% nest_dt("cyl|vs")
mtcars %>% nest_dt(c("cyl", "vs"))

# change the nested column name
mtcars %>% nest_dt(cyl, .name = "data")

# nest two columns directly
iris %>% nest_dt(mcols = list(petal="^Pe", sepal="^Se"))

# nest more flexibly
iris %>% nest_dt(mcols = list(ndt1 = 1:3,
  ndt2 = "Pe",
  ndt3 = Sepal.Length:Sepal.Width))

# examples for unnest_dt
```

```

# unnest which column?
mtcars %>% nest_dt("cyl|vs") %>%
  unnest_dt(ndt)
mtcars %>% nest_dt("cyl|vs") %>%
  unnest_dt("ndt")

df <- data.table(
  a = list(c("a", "b"), "c"),
  b = list(c(TRUE,TRUE),FALSE),
  c = list(3,c(1,2)),
  d = c(11, 22)
)

df
df %>% unnest_dt(a)
df %>% unnest_dt(2)
df %>% unnest_dt("c")
df %>% unnest_dt(cols = names(df)[3])

# You can unnest multiple columns simultaneously
df %>% unnest_dt(1:3)
df %>% unnest_dt(a,b,c)
df %>% unnest_dt("a|b|c")

# examples for squeeze_dt
# nest which columns?
iris %>% squeeze_dt(1:2)
iris %>% squeeze_dt("Se")
iris %>% squeeze_dt(Sepal.Length:Petal.Width)
iris %>% squeeze_dt(1:2,.name = "data")

# examples for chop_dt
df <- data.table(x = c(1, 1, 1, 2, 2, 3), y = 1:6, z = 6:1)
df %>% chop_dt(y,z)
df %>% chop_dt(y,z) %>% unchop_dt(y,z)

```

 nth

Extract the nth value from a vector

Description

nth get the value from a vector with its position, while maxth and minth get the nth highest or lowest value from the vector.

Usage

```
nth(v, n = 1)
```

```
maxth(v, n = 1)
```

```
minth(v, n = 1)
```


Arguments

v	A vector
n	For nth, a single integer specifying the position. Default uses 1. Negative integers index from the end (i.e. -1L will return the last value in the vector). If a double is supplied, it will be silently truncated. For maxth and minth, a single integer indicating the nth highest or lowest value.

Value

A single value.

References

<https://stackoverflow.com/questions/2453326/fastest-way-to-find-second-third-highest-lowest-value-in-vector-or-column/66367996#66367996>

Examples

```
x = 1:10
nth(x, 1)
nth(x, 5)
nth(x, -2)

y = c(10,3,4,5,2,1,6,9,7,8)
maxth(y,3)
minth(y,3)
```

object_size

Nice printing of report the Space Allocated for an Object

Description

Provides an estimate of the memory that is being used to store an R object. A wrapper of 'object.size', but use a nicer printing unit.

Usage

```
object_size(object)
```

Arguments

object an R object.

Value

An object of class "object_size"

Examples

```
iris %>% object_size()
```

pairwise_count_dt	<i>Count pairs of items within a group</i>
-------------------	--

Description

Count the number of times each pair of items appear together within a group. For example, this could count the number of times two words appear within documents. This function has referred to `pairwise_count` in **widyr** package, but with very different defaults on several parameters.

Usage

```
pairwise_count_dt(
  .data,
  .group,
  .value,
  upper = FALSE,
  diag = FALSE,
  sort = TRUE
)
```

Arguments

<code>.data</code>	A data.frame.
<code>.group</code>	Column name of counting group.
<code>.value</code>	Item to count pairs, will end up in V1 and V2 columns.
<code>upper</code>	When FALSE(Default), duplicated combinations would be removed.
<code>diag</code>	Whether to include diagonal (V1==V2) in output. Default uses FALSE.
<code>sort</code>	Whether to sort rows by counts. Default uses TRUE.

Value

A data.table with 3 columns (named as "V1", "V2" and "n"), containing combinations in "V1" and "V2", and counts in "n".

See Also

[pairwise_count](#)

Examples

```

dat <- data.table(group = rep(1:5, each = 2),
  letter = c("a", "b",
            "a", "c",
            "a", "c",
            "b", "e",
            "b", "f"))
pairwise_count_dt(dat,group,letter)
pairwise_count_dt(dat,group,letter,sort = FALSE)
pairwise_count_dt(dat,group,letter,upper = TRUE)
pairwise_count_dt(dat,group,letter,diag = TRUE)
pairwise_count_dt(dat,group,letter,diag = TRUE,upper = TRUE)

# The column name could be specified using character.
pairwise_count_dt(dat,"group","letter")

```

percent

*Add percentage to counts in data.frame***Description**

Add percentage for counts in the data.frame, both numeric and character with ‘

Usage

```

percent(x, digits = 1)

add_prop(.data, count_name = last(names(.data)), digits = 1)

```

Arguments

x	A number (numeric).
digits	How many digits to keep in the percentage. Default uses 1.
.data	A data frame.
count_name	Column name of counts (Character). Default uses the last column of data.frame.

References

<https://stackoverflow.com/questions/7145826/how-to-format-a-number-as-percentage-in-r>

Examples

```

percent(0.9057)
percent(0.9057,3)

iris %>%
  count_dt(Species) %>%
  add_prop()

```

```
iris %>%
  count_dt(Species) %>%
  add_prop(count_name = "n", digits = 2)
```

pkg_load	<i>Load or unload R package(s)</i>
----------	------------------------------------

Description

This function is a wrapper for [require](#) and [detach](#). `pkg_load` checks to see if a package is installed, if not it attempts to install the package from CRAN. `pkg_unload` can detach one or more loaded packages.

Usage

```
pkg_load(..., pkg_names = NULL)

pkg_unload(..., pkg_names = NULL)
```

Arguments

...	Name(s) of package(s).
pkg_names	(Optional)Character vector containing packages to load or unload. Default uses NULL.

See Also

[require](#), [detach](#), [p_load](#), [p_unload](#)

Examples

```
## Not run:
pkg_load(data.table)
pkg_unload(data.table)

pkg_load(stringr, fst)
pkg_unload(stringr, fst)

pkg_load(pkg_names = c("data.table", "fst"))
p_unload(pkg_names = c("data.table", "fst"))

pkg_load(data.table, stringr, fst)
pkg_unload("all") # shortcut to unload all loaded packages

## End(Not run)
```

print_options	<i>Set global printing method for data.table</i>
---------------	--

Description

This function allow user to define how data.table is printed.

Usage

```
print_options(  
  topn = 5,  
  nrow = 100,  
  class = TRUE,  
  row.names = TRUE,  
  col.names = "auto",  
  print.keys = TRUE,  
  trunc.cols = FALSE  
)
```

Arguments

topn	The number of rows to be printed from the beginning and end of tables with more than nrow rows.
nrow	The number of rows which will be printed before truncation is enforced.
class	If TRUE, the resulting output will include above each column its storage class (or a self-evident abbreviation thereof).
row.names	If TRUE, row indices will be printed.
col.names	One of three flavours for controlling the display of column names in output. "auto" includes column names above the data, as well as below the table if nrow(x) > 20. "top" excludes this lower register when applicable, and "none" suppresses column names altogether (as well as column classes if class = TRUE).
print.keys	If TRUE, any key currently assigned to x will be printed prior to the preview of the data.
trunc.cols	If TRUE, only the columns that can be printed in the console without wrapping the columns to new lines will be printed (similar to tibles).

Details

Notice that **tidyfst** has a slightly different printing default for data.table, which is it always prints the keys and variable class (not like **data.table**).

Value

None. This function is used for its side effect of changing options.

See Also[print.data.table](#)**Examples**

```
iris %>% as.data.table()
print_options(topn = 3, trunc.cols = TRUE)
iris %>% as.data.table()

# set all settings to default in tidyfst
print_options()
iris %>% as.data.table()
```

`pull_dt`*Pull out a single variable*

Description

Extract vector from data.frame, works likt '['. Analogous function for pull in **dplyr**

Usage

```
pull_dt(.data, col)
```

Arguments

<code>.data</code>	data.frame
<code>col</code>	A name of column or index (should be positive).

Value

vector

See Also[pull](#)**Examples**

```
mtcars %>% pull_dt(2)
mtcars %>% pull_dt(cyl)
mtcars %>% pull_dt("cyl")
```

rec	<i>Recode number or strings</i>
-----	---------------------------------

Description

Recode discrete variables, including numeric and character variable.

Usage

```
rec_num(x, rec, keep = TRUE)
```

```
rec_char(x, rec, keep = TRUE)
```

Arguments

x	A numeric or character vector.
rec	String with recode pairs of old and new values. Find the usage in examples.
keep	Logical. Decide whether to keep the original values if not recoded. Defaults to TRUE.

Value

A vector.

See Also

[rec](#)

Examples

```
x = 1:10
x
rec_num(x, rec = "1=10; 4=2")
rec_num(x, rec = "1:3=1; 4:6=2")
rec_num(x, rec = "1:3=1; 4:6=2", keep = FALSE)

y = letters[1:5]
y
rec_char(y, rec = "a=A;b=B")
rec_char(y, rec = "a,b=A;c,d=B")
rec_char(y, rec = "a,b=A;c,d=B", keep = FALSE)
```

relocate_dt	<i>Change column order</i>
-------------	----------------------------

Description

Change the position of columns, using the same syntax as `'select_dt()'`. Check similar function as `'relocate'` in **dplyr**.

Usage

```
relocate_dt(.data, ..., how = "first", where = NULL)
```

Arguments

<code>.data</code>	A <code>data.frame</code>
<code>...</code>	Columns to move
<code>how</code>	The mode of movement, including "first","last","after","before". Default uses "first".
<code>where</code>	Destination of columns selected by <code>...</code> . Applicable for "after" and "before" mode.

Value

A `data.table` with rearranged columns.

See Also

[relocate](#)

Examples

```
df <- data.table(a = 1, b = 1, c = 1, d = "a", e = "a", f = "a")
df
df %>% relocate_dt(f)
df %>% relocate_dt(a,how = "last")

df %>% relocate_dt(is.character)
df %>% relocate_dt(is.numeric, how = "last")
df %>% relocate_dt("[aeiou]")

df %>% relocate_dt(a, how = "after",where = f)
df %>% relocate_dt(f, how = "before",where = a)
df %>% relocate_dt(f, how = "before",where = c)
df %>% relocate_dt(f, how = "after",where = c)

df2 <- data.table(a = 1, b = "a", c = 1, d = "a")
df2 %>% relocate_dt(is.numeric,
                    how = "after",
```



```

                                where = is.character)
df2 %>% relocate_dt(is.numeric,
                    how="before",
                    where = is.character)

```

rename_dt	<i>Rename column in data.frame</i>
-----------	------------------------------------

Description

Rename one or more columns in the data.frame.

Usage

```

rename_dt(.data, ...)

rename_with_dt(.data, .fn, ...)

```

Arguments

.data	data.frame
...	statements of rename, e.g. 'sl = Sepal.Length' means the column named as "Sepal.Length" would be renamed to "sl"
.fn	A function used to transform the selected columns. Should return a character vector the same length as the input.

Value

data.table

See Also

[rename](#)

Examples

```

iris %>%
  rename_dt(sl = Sepal.Length,sw = Sepal.Width) %>%
  head()
iris %>% rename_with_dt(toupper)
iris %>% rename_with_dt(toupper,"^Pe")

```

replace_dt	<i>Fast value replacement in data frame</i>
------------	---

Description

While `replace_na_dt` could replace all NAs to another value, `replace_dt` could replace any value(s) to another specific value.

Usage

```
replace_dt(.data, ..., from = is.nan, to = NA)
```

Arguments

<code>.data</code>	A data.frame
<code>...</code>	Columns to be replaced. If not specified, use all columns.
<code>from</code>	A value, a vector of values or a function returns a logical value. Defaults to <code>is.nan</code> .
<code>to</code>	A value. Defaults to NA.

Value

A data.table.

See Also

[replace_na_dt](#)

Examples

```
iris %>% mutate_vars(is.factor,as.character) -> new_iris

new_iris %>%
  replace_dt(Species, from = "setosa",to = "SS")
new_iris %>%
  replace_dt(Species,from = c("setosa","virginica"),to = "sv")
new_iris %>%
  replace_dt(Petal.Width, from = .2,to = 2)
new_iris %>%
  replace_dt(from = .2,to = NA)
new_iris %>%
  replace_dt(is.numeric, from = function(x) x > 3, to = 9999 )
```

rn_col	<i>Tools for working with row names</i>
--------	---

Description

The enhanced data.frame, including tibble and data.table, do not support row names. To link to some base r facilities, there should be functions to save information in row names. These functions are analogous to rownames_to_column and column_to_rownames in **tibble**.

Usage

```
rn_col(.data, var = "rowname")
```

```
col_rn(.data, var = "rowname")
```

Arguments

.data	A data.frame.
var	Name of column to use for rownames.

Value

rn_col returns a data.table, col_rn returns a data frame.

Examples

```
mtcars %>% rn_col()
mtcars %>% rn_col("rn")

mtcars %>% rn_col() -> new_mtcars

new_mtcars %>% col_rn() -> old_mtcars
old_mtcars
setequal(mtcars,old_mtcars)
```

round0	<i>Round a number and make it show zeros</i>
--------	--

Description

Rounds values in its first argument to the specified number of decimal places, returning character, ensuring first decimal digits are showed even when they are zeros.

Usage

```
round0(x, digits = 0)
```

Arguments

x A numeric vector.
digits Integer indicating the number of decimal places. Defaults to 0.

Value

A character vector.

References

<https://stackoverflow.com/questions/42105336/how-to-round-a-number-and-make-it-show-zeros>

See Also

[round](#)

Examples

```
a = 14.0034
round0(a,2)

b = 10
round0(b,1)
```

sample_dt

Sample rows randomly from a table

Description

Select a number or proportion of rows randomly from the data frame

sample_dt is a merged version of sample_n_dt and sample_frac_dt, this could be convenient.

Usage

```
sample_dt(.data, n = NULL, prop = NULL, replace = FALSE, by = NULL)
```

```
sample_n_dt(.data, size, replace = FALSE, by = NULL)
```

```
sample_frac_dt(.data, size, replace = FALSE, by = NULL)
```

Arguments

.data	A data.frame
n	Number of rows to select
prop	Fraction of rows to select
replace	Sample with or without replacement? Default uses FALSE.
by	(Optional) Character. Specify if you want to sample by group.
size	For sample_n_dt, the number of rows to select. For sample_frac_dt, the fraction of rows to select.

Value

data.table

See Also

[sample_n](#), [sample_frac](#)

Examples

```
sample_n_dt(mtcars, 10)
sample_n_dt(mtcars, 50, replace = TRUE)
sample_frac_dt(mtcars, 0.1)
sample_frac_dt(mtcars, 1.5, replace = TRUE)

sample_dt(mtcars, n=10)
sample_dt(mtcars, prop = 0.1)

# sample by group(s)
iris %>% sample_n_dt(2, by = "Species")
iris %>% sample_frac_dt(.1, by = "Species")

mtcars %>% sample_n_dt(1, by = c("cyl", "vs"))
```

select_dt	<i>Select column from data.frame</i>
-----------	--------------------------------------

Description

Select specific column(s) via various ways. One can select columns by their column names, indexes or regular expression recognizing the column name(s).

Usage

```
select_dt(.data, ..., cols = NULL, negate = FALSE)

select_mix(.data, ..., rm.dup = TRUE)
```

Arguments

<code>.data</code>	data.frame
<code>...</code>	List of variables or name-value pairs of summary/modifications functions. It can also receive conditional function to select columns. When starts with '-' (minus symbol) or 'i', return the negative columns.
<code>cols</code>	(Optional) A numeric or character vector.
<code>negate</code>	Applicable when regular expression and "cols" is used. If TRUE, return the non-matched pattern. Default uses FALSE.
<code>rm.dup</code>	Should duplicated columns be removed? Defaults to TRUE.

Value

data.table

See Also

[select](#), [select_if](#)

Examples

```
iris %>% select_dt(Species)
iris %>% select_dt(Sepal.Length, Sepal.Width)
iris %>% select_dt(Sepal.Length:Petal.Length)
iris %>% select_dt(-Sepal.Length)
iris %>% select_dt(-Sepal.Length, -Petal.Length)
iris %>% select_dt(-(Sepal.Length:Petal.Length))
iris %>% select_dt(c("Sepal.Length", "Sepal.Width"))
iris %>% select_dt(-c("Sepal.Length", "Sepal.Width"))
iris %>% select_dt(1)
iris %>% select_dt(-1)
iris %>% select_dt(1:3)
iris %>% select_dt(-(1:3))
iris %>% select_dt(1,3)
iris %>% select_dt("Pe")
iris %>% select_dt("-Se")
iris %>% select_dt(!"Se")
iris %>% select_dt("Pe", negate = TRUE)
iris %>% select_dt("Pe|Sp")
iris %>% select_dt(cols = 2:3)
iris %>% select_dt(cols = 2:3, negate = TRUE)
iris %>% select_dt(cols = c("Sepal.Length", "Sepal.Width"))
iris %>% select_dt(cols = names(iris)[2:3])

iris %>% select_dt(is.factor)
iris %>% select_dt(-is.factor)
iris %>% select_dt(!is.factor)

# select_mix could provide flexible mix selection
select_mix(iris, Species, "Sepal.Length")
select_mix(iris, 1:2, is.factor)
```

```
select_mix(iris,Sepal.Length,is.numeric)
# set rm.dup to FALSE could save the duplicated column names
select_mix(iris,Sepal.Length,is.numeric,rm.dup = FALSE)
```

separate_dt	<i>Separate a character column into two columns using a regular expression separator</i>
-------------	--

Description

Given either regular expression, `separate_dt()` turns a single character column into two columns.

Usage

```
separate_dt(
  .data,
  separated_colname,
  into,
  sep = "[^[:alnum:]]+",
  remove = TRUE
)
```

Arguments

<code>.data</code>	A data frame.
<code>separated_colname</code>	Column to be separated, can be a character or alias.
<code>into</code>	Character vector of length 2.
<code>sep</code>	Separator between columns.
<code>remove</code>	If TRUE, remove input column from output data frame.

See Also

[separate](#), [unite_dt](#)

Examples

```
df <- data.frame(x = c(NA, "a.b", "a.d", "b.c"))
df %>% separate_dt(x, c("A", "B"))
# equals to
df %>% separate_dt("x", c("A", "B"))

# If you just want the second variable:
df %>% separate_dt(x,into = c(NA,"B"))
```

slice_dt *Subset rows using their positions*

Description

'slice_dt()' lets you index rows by their (integer) locations. It allows you to select, remove, and duplicate rows. It is accompanied by a number of helpers for common use cases:

* 'slice_head_dt()' and 'slice_tail_dt()' select the first or last rows. * 'slice_sample_dt()' randomly selects rows. * 'slice_min_dt()' and 'slice_max_dt()' select rows with highest or lowest values of a variable.

Usage

```
slice_dt(.data, ..., by = NULL)

slice_head_dt(.data, n, by = NULL)

slice_tail_dt(.data, n, by = NULL)

slice_max_dt(.data, order_by, n, by = NULL, with_ties = TRUE)

slice_min_dt(.data, order_by, n, by = NULL, with_ties = TRUE)

slice_sample_dt(.data, n, replace = FALSE, by = NULL)
```

Arguments

.data	A data.table
...	Provide either positive values to keep, or negative values to drop. The values provided must be either all positive or all negative.
by	Slice by which group(s)?
n	When larger than or equal to 1, the number of rows. When between 0 and 1, the proportion of rows to select.
order_by	Variable or function of variables to order by.
with_ties	Should ties be kept together? The default, 'TRUE', may return more rows than you request. Use 'FALSE' to ignore ties, and return the first 'n' rows.
replace	Should sampling be performed with ('TRUE') or without ('FALSE', the default) replacement.

Value

A data.table

See Also

[slice](#)

Examples

```

a = iris
slice_dt(a,1,2)
slice_dt(a,2:3)
slice_dt(a,141:.N)
slice_dt(a,1,.N)
slice_head_dt(a,5)
slice_head_dt(a,0.1)
slice_tail_dt(a,5)
slice_tail_dt(a,0.1)
slice_max_dt(a,Sepal.Length,10)
slice_max_dt(a,Sepal.Length,10,with_ties = FALSE)
slice_min_dt(a,Sepal.Length,10)
slice_min_dt(a,Sepal.Length,10,with_ties = FALSE)
slice_sample_dt(a,10)
slice_sample_dt(a,0.1)

# use by to slice by group

## following codes get the same results
slice_dt(a,1:3,by = "Species")
slice_dt(a,1:3,by = Species)
slice_dt(a,1:3,by = .(Species))

slice_head_dt(a,2,by = Species)
slice_tail_dt(a,2,by = Species)

slice_max_dt(a,Sepal.Length,3,by = Species)
slice_max_dt(a,Sepal.Length,3,by = Species,with_ties = FALSE)
slice_min_dt(a,Sepal.Length,3,by = Species)
slice_min_dt(a,Sepal.Length,3,by = Species,with_ties = FALSE)

# in `slice_sample_dt`, "by" could only take character class
slice_sample_dt(a,.1,by = "Species")
slice_sample_dt(a,3,by = "Species")
slice_sample_dt(a,51,replace = TRUE,by = "Species")

```

sql_join

Case insensitive table joining like SQL

Description

Work like the ‘*_join_dt’ series functions, joining tables with common or customized keys in various ways. The only difference is the joining is case insensitive like SQL.

Usage

```
sql_join_dt(x, y, by = NULL, type = "inner", suffix = c(".x", ".y"))
```

Arguments

x	A data.table
y	A data.table
by	(Optional) A character vector of variables to join by. If 'NULL', the default, '*_join_dt()' will perform a natural join, using all variables in common across 'x' and 'y'. A message lists the variables so that you can check they're correct; suppress the message by supplying 'by' explicitly. To join by different variables on 'x' and 'y', use a named vector. For example, 'by = c("a" = "b")' will match 'x\$a' to 'y\$b'. To join by multiple variables, use a vector with length > 1. For example, 'by = c("a", "b")' will match 'x\$a' to 'y\$a' and 'x\$b' to 'y\$b'. Use a named vector to match different variables in 'x' and 'y'. For example, 'by = c("a" = "b", "c" = "d")' will match 'x\$a' to 'y\$b' and 'x\$c' to 'y\$d'. Notice that in 'sql_join', the joining variables would turn to upper case in the output table.
type	Which type of join would you like to use? Default uses "inner", other options include "left", "right", "full", "anti", "semi".
suffix	If there are non-joined duplicate variables in x and y, these suffixes will be added to the output to disambiguate them. Should be a character vector of length 2.

Value

A data.table

See Also

[join](#)

Examples

```
dt1 = data.table(x = c("A", "b"), y = 1:2)
dt2 = data.table(x = c("a", "B"), z = 4:5)
sql_join_dt(dt1, dt2)
```

summarise_dt

Summarise columns to single values

Description

Summarise group of values into one value for each group. If there is only one group, then only one value would be returned. The summarise function should always return a single value.

Usage

```

summarise_dt(.data, ..., by = NULL)

summarize_dt(.data, ..., by = NULL)

summarise_when(.data, when, ..., by = NULL)

summarize_when(.data, when, ..., by = NULL)

summarise_vars(.data, .cols = NULL, .func, ..., by)

summarize_vars(.data, .cols = NULL, .func, ..., by)

```

Arguments

<code>.data</code>	<code>data.frame</code>
<code>...</code>	List of variables or name-value pairs of summary/modifications functions for <code>summarise_dt</code> . Additional parameters to be passed to parameter <code>'func'</code> in <code>summarise_vars</code> .
<code>by</code>	unquoted name of grouping variable or list of unquoted names of grouping variables. For details see data.table
<code>when</code>	An object which can be coerced to logical mode
<code>.cols</code>	Columns to be summarised.
<code>.func</code>	Function to be run within each column, should return a value or vectors with same length.

Details

`summarise_vars` could complete summarise on specific columns.

Value

`data.table`

See Also

[summarise](#)

Examples

```

iris %>% summarise_dt(avg = mean(Sepal.Length))
iris %>% summarise_dt(avg = mean(Sepal.Length), by = Species)
mtcars %>% summarise_dt(avg = mean(hp), by = .(cyl, vs))

# the data.table way
mtcars %>% summarise_dt(cyl_n = .N, by = .(cyl, vs)) # `.` is short for list

iris %>% summarise_vars(is.numeric, min)
iris %>% summarise_vars(-is.factor, min)

```

```
iris %>% summarise_vars(1:4,min)

iris %>% summarise_vars(is.numeric,min,by ="Species")
mtcars %>% summarise_vars(is.numeric,mean,by = c(">vs", "am"))

# use multiple functions on multiple columns
iris %>%
  summarise_vars(is.numeric,.func = list(mean,sd,median))
iris %>%
  summarise_vars(is.numeric,.func = list(mean,sd,median),by = Species)
```

sys_time_print	<i>Convenient print of time taken</i>
----------------	---------------------------------------

Description

Convenient printing of time elapsed. A wrapper of `data.table::timetaken`, but showing the results more directly.

Usage

```
sys_time_print(expr)

pst(expr)
```

Arguments

`expr` Valid R expression to be timed.

Value

A character vector of the form `HH:MM:SS`, or `SS.MMMsec` if under 60 seconds (invisibly for `show_time`). See examples.

See Also

[timetaken](#), [system.time](#)

Examples

```
sys_time_print(Sys.sleep(1))

a = iris
sys_time_print({
  res = iris %>%
    mutate_dt(one = 1)
})
res
```

t_dt	<i>Efficient transpose of data.frame</i>
------	--

Description

An efficient way to transpose data frames(data.frame/data.table/tibble).

Usage

```
t_dt(.data)
```

Arguments

.data	A data.frame/data.table/tibble
-------	--------------------------------

Details

This function would return the original data.frame structure, keeping all the row names and column names. If the row names are not available or, "V1,V2..." will be provided.

Value

A transposed data.frame

Examples

```
t_dt(iris)
t_dt(mtcars)
```

uncount_dt	<i>"Uncount" a data frame</i>
------------	-------------------------------

Description

Duplicating rows according to a weighting variable. This is the opposite operation of 'count_dt'. Analogous to 'tidyr::uncount'.

Usage

```
uncount_dt(.data, wt, .remove = TRUE)
```

Arguments

.data	A data.frame
wt	A vector of weights.
.remove	Should the column for weights be removed? Default uses TRUE.

See Also

[count](#), [uncount](#)

Examples

```
df <- data.table(x = c("a", "b"), n = c(1, 2))
uncount_dt(df, n)
uncount_dt(df,n,FALSE)
```

unite_dt

Unite multiple columns into one by pasting strings together

Description

Convenience function to paste together multiple columns into one.

Usage

```
unite_dt(
  .data,
  united_colname,
  ...,
  sep = "_",
  remove = FALSE,
  na2char = FALSE
)
```

Arguments

<code>.data</code>	A data frame.
<code>united_colname</code>	The name of the new column, string only.
<code>...</code>	A selection of columns. If want to select all columns, pass "" to the parameter. See example.
<code>sep</code>	Separator to use between values.
<code>remove</code>	If TRUE, remove input columns from output data frame.
<code>na2char</code>	If FALSE, missing values would be merged into NA, otherwise NA is treated as character "NA". This is different from tidyr .

See Also

[unite](#), [separate_dt](#)

Examples

```
df <- expand.grid(x = c("a", NA), y = c("b", NA))
df

# Treat missing value as NA, default
df %>% unite_dt("z", x:y, remove = FALSE)
# Treat missing value as character "NA"
df %>% unite_dt("z", x:y, na2char = TRUE, remove = FALSE)
df %>%
  unite_dt("xy", x:y)

# Select all columns
iris %>% unite_dt("merged_name", ".")
```

utf8_encoding	<i>Use UTF-8 for character encoding in a data frame</i>
---------------	---

Description

read from **data.table** could not recognize the encoding and return the correct form, this could be inconvenient for text mining tasks. The utf8-encoding could use "UTF-8" as the encoding to override the current encoding of characters in a data frame.

Usage

```
utf8_encoding(.data)
```

Arguments

.data A data.frame.

Value

A data.table with characters in UTF-8 encoding

wider_dt	<i>Pivot data from long to wide</i>
----------	-------------------------------------

Description

Transform a data frame from long format to wide by increasing the number of columns and decreasing the number of rows.

Usage

```
wider_dt(.data, ..., name, value = NULL, fun = NULL, fill = NA)
```

Arguments

<code>.data</code>	A <code>data.frame</code>
<code>...</code>	Optional. The unchanged group in the transformation. Could use integer vector, could receive what <code>select_dt</code> receives.
<code>name</code>	Character. One column name of class to spread
<code>value</code>	Character. One column name of value to spread. If NULL, use all other variables.
<code>fun</code>	Should the data be aggregated before casting? Defaults to NULL, which uses length for aggregation. If a function is provided, with aggregated by this function.
<code>fill</code>	Value with which to fill missing cells. Default uses NA.

Details

The parameter of 'name' and 'value' should always be provided and should be explicit called (with the parameter names attached).

Value

`data.table`

See Also

[longer_dt](#), [dcast](#), [pivot_wider](#)

Examples

```
stocks = data.frame(
  time = as.Date('2009-01-01') + 0:9,
  X = rnorm(10, 0, 1),
  Y = rnorm(10, 0, 2),
  Z = rnorm(10, 0, 4)
) %>%
  longer_dt(time) -> longer_stocks

longer_stocks

longer_stocks %>%
  wider_dt("time",
          name = "name",
          value = "value")

longer_stocks %>%
  mutate_dt(one = 1) %>%
  wider_dt("time",
          name = "name",
          value = "one")

## using "fun" parameter for aggregation
DT <- data.table(v1 = rep(1:2, each = 6),
```



```
      v2 = rep(rep(1:3, 2), each = 2),
      v3 = rep(1:2, 6),
      v4 = rnorm(6))
## for each combination of (v1, v2), add up all values of v4
DT %>%
  wider_dt(v1,v2,
    value = "v4",
    name = ".",
    fun = sum)
```

`%notin%`*Not in operator*

Description

Inverse operation of `match`.

Usage

```
x %notin% y
```

Arguments

x	vector or NULL
y	vector or NULL

Examples

```
"a" %in% letters[1:3]
"a" %notin% letters[1:3]

1 %in% 1:3
1 %notin% 1:3
```

Index

`%notin%`, 57

`add_count_dt` (`count_dt`), 7

`add_prop` (`percent`), 35

`anti_join_dt` (`join`), 23

`arrange`, 3

`arrange_dt`, 3

`as_dt` (`in_dt`), 22

`as_fst`, 4

`bind_rows`, 5

`bind_rows_dt`, 4

`case_when`, 30

`chop`, 31

`chop_dt` (`nest_dt`), 30

`col_max`, 5

`col_min` (`col_max`), 5

`col_rn` (`rn_col`), 43

`complete`, 7

`complete_dt`, 6

`count`, 7, 54

`count_dt`, 7

`cummean`, 8

`data.table`, 23, 51

`dcast`, 56

`delete_na_cols` (`drop_na_dt`), 9

`delete_na_rows` (`drop_na_dt`), 9

`detach`, 36

`df_mat` (`mat_df`), 27

`distinct`, 9

`distinct_dt`, 8

`drop_na`, 10

`drop_na_dt`, 9

`dummy_cols`, 12

`dummy_dt`, 11

`export_fst`, 12

`fill`, 10

`fill_na_dt` (`drop_na_dt`), 9

`filter`, 14

`filter_dt`, 14

`filter_fst` (`fst`), 15

`fst`, 15, 15

`full_join_dt` (`join`), 23

`get_fst_chunk_size`
(`import_fst_chunked`), 19

`group_by_dt`, 16

`group_dt`, 17

`group_exe_dt` (`group_by_dt`), 16

`import_fst` (`export_fst`), 12

`import_fst_chunked`, 19

`impute_dt`, 20

`in_dt`, 22

`inner_join_dt` (`join`), 23

`intersect_dt`, 21

`join`, 23, 50

`key`, 37

`lag_dt` (`lead_dt`), 25

`lead`, 26

`lead_dt`, 25

`left_join_dt` (`join`), 23

`longer_dt`, 26, 56

`mat_df`, 27

`maxth` (`nth`), 32

`melt`, 26

`metadata_fst`, 15

`minth` (`nth`), 32

`mutate`, 29

`mutate_dt`, 28

`mutate_vars` (`mutate_when`), 29

`mutate_when`, 29

`nest`, 31

nest_dt, 30
nth, 32

object_size, 33

p_load, 36
p_unload, 36
pairwise_count, 34
pairwise_count_dt, 34
parse_fst (fst), 15
percent, 35
pivot_longer, 26
pivot_wider, 56
pkg_load, 36
pkg_unload (pkg_load), 36
print.data.table, 38
print_options, 37
pst (sys_time_print), 52
pull, 38
pull_dt, 38

rbindlist, 5
read_csv_chunked, 20
read_fst, 12, 13
rec, 39, 39
rec_char (rec), 39
rec_num (rec), 39
relocate, 40
relocate_dt, 40
rename, 41
rename_dt, 41
rename_with_dt (rename_dt), 41
replace_dt, 42
replace_na, 10
replace_na_dt, 42
replace_na_dt (drop_na_dt), 9
require, 36
right_join_dt (join), 23
rn_col, 43
round, 44
round0, 43
rowwise_dt (group_dt), 17

sample_dt, 44
sample_frac, 45
sample_frac_dt (sample_dt), 44
sample_n, 45
sample_n_dt (sample_dt), 44
select, 46
select_dt, 6, 29, 30, 45
select_fst (fst), 15
select_if, 46
select_mix (select_dt), 45
semi_join_dt (join), 23
separate, 47
separate_dt, 47, 54
setdiff_dt (intersect_dt), 21
setequal_dt (intersect_dt), 21
setops, 22
shift, 26
shift_fill (drop_na_dt), 9
slice, 48
slice_dt, 48
slice_fst (fst), 15
slice_head_dt (slice_dt), 48
slice_max_dt (slice_dt), 48
slice_min_dt (slice_dt), 48
slice_sample_dt (slice_dt), 48
slice_tail_dt (slice_dt), 48
sql_join, 49
sql_join_dt (sql_join), 49
squeeze_dt (nest_dt), 30
summarise, 51
summarise_dt, 50
summarise_vars (summarise_dt), 50
summarise_when (summarise_dt), 50
summarize_dt (summarise_dt), 50
summarize_vars (summarise_dt), 50
summarize_when (summarise_dt), 50
summary_fst (fst), 15
sys_time_print, 52
system.time, 52

t_dt, 53
timetaken, 52
transmute_dt (mutate_dt), 28

unchop_dt (nest_dt), 30
uncount, 54
uncount_dt, 53
union_dt (intersect_dt), 21
unite, 54
unite_dt, 47, 54
unnest_dt (nest_dt), 30
utf8_encoding, 55

wider_dt, 26, 55
write_fst, 12